

## SUBMARINE SINGLE CARCASS 15 bar 1000 Series

### Type 1622S Mainline Hose With Location Collars



Nominal Bore (mm)	Collar Outside Diameter (mm)				Weight in Air Empty (kg)			Minimum Bending Radius (m)
	D1		D2		Submerged Weight Full of Sea Water (kg)			
	Body	End	9.1m (30ft)	10.7m (35ft)	12.2m (40ft)			
150 (6")	310	420	-	-	572 175	646 191	715 207	0.6
200 (8")	370	471	-	-	744 233	841 255	931 276	0.8
250 (10")	420	581	-	-	997 329	1122 358	1239 386	1.0
300 (12")	471	581	-	-	1239 461	1398 505	1548 547	1.2
400 (16")	581	697	-	-	1737 683	1955 747	2161 806	1.6
500 (20")	697	799	-	-	2316 929	2612 1017	2890 1099	2.0
600 (24")	799	946	-	-	3024 1246	3416 1370	3784 1487	2.4

- Single Carcass Hose FLEXOMARINE Mainline Standard Submarine Hose for use as the main submarine hose in the string to connect between sea bed manifold and buoy connection used on monobuoy systems
- Supplied with float location collars
- Rated Working Pressure: 15 bar
- Minimum Bending Radius: 4D (up to 2D without any permanent deformation)
- Electrical Continuity: Discontinuous or as requested